

E747 ENCODER




Activation Control

E747 FEATURES

Ideal for small warning systems and easy to use. The E747 encoder aids dispatchers in quickly activating mass notification products when disaster strikes. The E747 is provided in a compact and attractive desktop design for applications where space is at a premium.

- Simple 3 step operation
 1. Select command
 2. Select individual unit or "All Call"
 3. Press send
- Whelen 10 digit DTMF activation protocol is fast, secure and reliable
- Selection of 18 activation commands
- Selection of 1-10 units individually
- System "All Call"
- Inclined keyboard for easy access and viewing
- Membrane keypad features raised keys with tactile response
- LED indicators illuminate upon key selection
- Command key LED flashes when activation has been sent
- Keyboard On/Off switch and LED indicator
- Microphone input and microphone level adjustment
- May be used for mobile applications



E747 ENCODER



Specification Data

SPECIFICATION DATA

E747: 18 function encoder permitting individual selection of 1-10 units or system "All Call". Compact desktop design with inclined sealed membrane keyboard. LED key select indicators illuminate upon key selection. Command key LED flashes upon transmission of activation sequence. 12VDC nominal operation, furnished with UL listed wall mount transformer. May be used for mobile applications.

PHYSICAL DATA

Height: 2.1"
Width: 6.9"
Depth: 6.7" (including mic plug)
Weight: 1.1 lb.

ELECTRICAL DATA

Power: 12VDC, nominal. The E747 is furnished with a UL listed 120VAC/12VDC wall mount transformer.

Current: 60ma 12VDC typical, 150ma maximum.

Microphone: Ground, signal, PTT.

Outputs: 4 wire cable, audio - 2 wires, PTT - 2 wires.

Audio: 2 wire, 600 ohm transformer balanced, output adjustable 0-2v P-P.

Control: 2 wire, transmitter PTT.

SIGNALLING

1 N.O. relay contact. Contact rating: 1/2a @ 120VAC, 1a @ 12VDC.

DTMF 2 of 8 format, Whelen 10 digit protocol.

REAR PANEL CONTROLS

Transmitter Warmup:
4 selections: 100ms, 500ms, 1 sec. & 2 sec.

DTMF Tone Level:
Variable, 0-4vpp.

Microphone Level:
Variable, 0-6vpp.

ENVIRONMENTAL DATA

Operating Temperature:
-20°C to +60°C.

Storage Temperature:
-40°C to +60°C.

Humidity:
0-90% non-condensing.

ORDERING INFORMATION

E747: 18 Function

Optional WPSMIC: Microphone


MASS NOTIFICATION PRODUCTS

Whelen Engineering Company, Inc.
51 Winthrop Road
Chester, Connecticut 06412-0684
860-526-9504
800-637-4736
www.whelen.com
iowsales@whelen.com

Whelen Engineering Company, Inc.
reserves the right to upgrade its products with
design improvements without notification.
© 2019 Whelen Engineering Company, Inc.
Printed in the U.S.A.
10941H-09/25/19



*"Our Mass Notification Products
Speak for Themselves"™*

 **WARNING:** This product may contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit whelen.com/regulatory.